

Appln No. 10/760255
Amdt. Dated: January 31, 2007
Response to Office Action of November 24, 2006

4

REMARKS/ARGUMENTS

Applicant thanks Examiner for the detailed Office Action dated November 24, 2006. In response to the issues raised, the Applicant offers the following submissions and amendments.

Amendments

Claim 1 clarifies the data processing role of the controller(s) in each module and the function of the drive electronics in relation to the printhead assembly as a whole. These features are described in detail at page 15, line 25 to page 16, line 9, and page 19, lines 10 to 15.

Accordingly, the amendments do not add any new matter.

35 U.S.C. §103 - Claims 1 to 5

Claims 1 to 5 stand rejected as obvious in light of US 6,439,908 to Silverbrook et al in view of US 6,443,555 to Silverbrook. Amended claim 1 distinguishes these disclosures by highlighting that the printhead assembly of the present invention has printhead modules that each have one or more of their own print engine controllers (PECs). The skilled addressee, reading the claims in light of the specification as a whole, would understand that the controllers are micro-processors that send the fire signals to the nozzles on the printhead IC(s) which it controls. Amended claim 1 specifies that the controller and its relevant printhead IC(s) are separate devices by defining that the print data is transmitted using a device addressing protocol.

As described at page 15, lines 25 to 37, the drive electronics can support several controllers, and this has a direct bearing on the operating speed of the printhead IC's. In the embodiment described, one PEC drives four printhead IC's to achieve the desired print speed. However, this ratio can be altered so the print speed can be suited to a wide range of printing applications. Furthermore, this modular approach to the control circuitry makes it easy to identify and replace defective electronics.

In the '908 patent, each module 12 has a single printhead chip 18. The modules can be individually removed and replaced so that the entire pagewidth printhead is not scrapped because of nozzle failure in one chip. Furthermore, '908 does not describe the print engine controller that drives the printhead IC's. Only the data connector 66 is discussed. The PEC is not part of the printhead assembly 10 taught by '908.

The '555 patent is directed to a wide format printer. It also uses printhead modules 1 that have a single printhead IC 2 each. Ten modules 2 are mounted to a printhead unit 3. Each unit 3 has only one PEC 18. It does not contemplate an arrangement that allows the ratio of PEC to printhead ICs to be varied.

Accordingly, '908 and '55 do not teach fundamental elements of amended claim 1. In light of this, the cited references fail to anticipate the invention defined by any of claims 1 to 5.

Appln No. 10/760255
Amdt. Dated: January 31, 2007
Response to Office Action of November 24, 2006

5


Conclusion

It is respectfully submitted that the Examiner's rejection has been successfully traversed and the application is now in condition for allowance. Accordingly, favorable reconsideration is courteously solicited.

Very respectfully,

Applicant/s:



Kia Silverbrook

Norman Micheal Berry

Garry Raymond Jackson

Akira Nakazawa

C/o: Silverbrook Research Pty Ltd
393 Darling Street
Balmain NSW 2041, Australia

Email: kia.silverbrook@silverbrookresearch.com

Telephone: +612 9818 6633

Facsimile: +61 2 9555 7762